

PN3211 UVD

2-Channel UV Detector



PN3211 UV Detector

Features

The PN3211 2-channel UV Detector provides an exceptional level of sensitivity and stability. As a high sensitive UV detector, the PN3211 has a noise level of 0.5×10^{-5} AU max., making it to one of most sensitive UV detectors (ASTM Standards).

- Greater Baseline Stability**
Supplied as standard, a temperature-controlled flow cell eliminates inconsistencies caused by changes in absorbance due to shifts in room temperature. This helps increase the baseline stability and the analysis reliability.
- Superior Linearity ≥ 2 AU**
Using newly developed signal processing technology, the stray-light correction function has been enhanced, and the linearity has been improved. This expanded linearity combines various noise-reduction technologies to provide users with a wide dynamic range and allows the analysis of your target compound and minor impurities in a single run.
- Internal Validation Protocol**
The incorporation of a low-pressure mercury lamp for wavelength calibration ensures simple calibration in the ultraviolet region.
- Dual-Wavelength Measurement**
Monitor two components in the UV range simultaneously.

Ordering Information

S-DET-3211-001	PN3211 UV Detector
Flow Cells	
Z-DET-3211-001	Analytical, Peek
Z-DET-3211-002	Analytical, Stainless Steel
Z-DET-3211-003	Preparative, Stainless Steel
Detector Lamps	
Z-DL-PN3211	D2-Lamp, Pre-aligned, Longlife

Specifications

- Light Source:
Deuterium lamp
- Wavelength Range:
190 – 700 nm
- Wavelength Accuracy:
 ± 1 nm
- Noise Level:
 $\pm 0.25 \times 10^{-5}$ AU max.
- Drift:
1 x 10^{-4} AU/h max.
(250 nm, room temperature constant, air in cell)
3 x 10^{-4} AU/h max.
(250 nm, room temperature fluctuation less than 2°C, air in cell)
- Operating Temperature:
4 - 35°C
- Cell Temperature Range:
5°C above room temperature to 50°C, at 1°C steps
- Response:
11 steps selectable (corresponding to time constant 0.02, 0.05, 0.1, 0.5, 1.0, 1.5, 2.0, 3.0, 6.0, 8.0, 10.0 sec)
- Range:
0.0001 – 2.56 AUFS
(selectable in 0.0001 AUSF steps)
- Zero Adjustment:
Auto zero function
baseline shift function
- Wavelength Steps:
1–5 nm, selectable in 5 steps
2–5 nm when W lamp is used
- Scanning Speed:
10 – 50 nm/sec, in 5 steps
- Spectrum Plot:
output speed 1, 3, 10 nm/sec
- Optical Path Length:
10 mm
- Cell Volume:
12 μ L
- Pressure Resistance:
12 MPa
- Wetted Surface Materials:
SUS316L, quartz, PFA
- Dimensions (WxHxD):
260 x 140 x 420 mm
- Weight:
13 Kg
- Power Requirements:
100/120/220-240 V, 50/60Hz

Contact

- Postnova Analytics GmbH
86899 Landsberg, GERMANY
T: +49 8191 985 688 0
- Postnova Analytics UK Ltd.
Malvern, Worcestershire, WR14 3SZ, UK
T: +44 1684 585167
- Postnova Analytics Inc.
Salt Lake City, UT 84102, USA
T: +1 801 521 2004

info@postnova.com
www.postnova.com